



# **KÖSTER Special Caulking Gun**

**Technical Data Sheet J 981** 

Prod. code IN 959 001

Prod. code X 987 001

Prod. code J 250

Issued: 2021-03-31

# Caulking gun for installing 530 ml / 850 g KÖSTER KB-Flex 200 Cartridges

Hand pistol

**Related products** 

KÖSTER Spatula

Flexible, soft attachment

Barrel length 375 mm

KÖSTER Cleaning Brush

KÖSTER KB-Flex 200

Stiff, 45 °elbow attachment

# Features

The KÖSTER Special Caulking Gun is a robust and reliable hand injection pump for installing 530 ml / 850 g KÖSTER KB-Flex 200 cartridges.

# **Technical Data**

Mechanical Thrust ratio Distance per stroke Maximum force Cartridge capacity Weight Carriage length 12:1 7 mm 2.5 kN 310-530ml 1.05 kg (2.31 lbs) 375 mm (14.78")

#### **Fields of Application**

For more information see the Technical Guideline for KÖSTER KB-Flex 200.

Advantages: Patented adjustable screw to cut thrust gaps Dripless design Suitable for Low and Medium viscosity materials

Product Description: Aluminum alloy handle / Steel trigger Twin heat treatment steel push plates Steel zinc plated push rod 360 ° Rotary type of Anodized Aluminum barrel 1.5mm steel zinc plated push piston Built-in cartridge puncture tool Pull handle is "T" shaped Includes standard nozzle and Instruction manual Packing: 1pce/ PE bag, 10pcs/ carton

## Cleaning

After use clean the KÖSTER Special Caulking Gun, tools and any residues with a cloth or paper towels, oily residue can be removed with KÖSTER Universal Cleaner.

#### Packaging

J 981 001

piece

#### Storage

When stored clean and dry there is no limited storage time.

#### Safety

Observe all Local, State, and Governmental saftety requirements when using tools of all types.

# Other

Basic equipment/Scope of delivery

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax -40 • info@koester.eu • www.koester.eu